Artemide

PRODUCT DATA SHEET

Altrove TW Suspension - Direct/indirect Light



DESIGN BY:

Carlotta de Bevilacqua 2010

MATERIALS:

Steel, Prismoptic, aluminium, methacrylate, PETG

DESCRIPTION:

In a m2 of surface where the light flows in a fluid way on transparent wires and, through a mirrored reflector, materializes a lighting and volumetric effect wich is controlled. It is a cubic metre of light where everything is endlessly reflected, freely modulating more than a million of chromatic effects. The space is no more just one, but several, or simply "else", illusory perception of reality, which drives to a new place, elsewhere. Three versions are available, with three kind of light. Opening light: perimeter structure made of steel, top side mirror reflector, side diffusers made of opaline methacrylate, front diffuser in transparent engraved methacrylate. Volumetric light: perimeter structure made of steel, top side segment reflector, side diffusers made of opaline methacrylate, front diffuser in transparent engraved methacrylate. Fluid light: perimeter structure made of steel, side diffusers made of opaline methacrylate, front diffuser in transparent engraved methacrylate.



MYWHITELIGHT

PRODUCT CODE 1648010A

Light emission



Dimmable

RF remote control included.

Altrove TW Suspension -Direct/indirect Light 1648010A

Steel, Prismoptic, aluminium, methacrylate,

Design, My White Light

Mirror

PETG

Indoor

Diffused

cm 100 cm 100

cm 10 cm 200 N.D.

850 °

TECHNICAL DATA SHEET

FEATURES

Product name:

Article Code: Colour: Material:

Series: Environment:

OPTICS


Emission:

DIMENSIONS

Length:	
Width:	
Height:	
Max Height from ceiling:	
Impact Resistance:	
Glow Wire Test:	

LAMPS INCLUDED

Category:	FLUO
Number:	2
Lbs:	T16
Watt:	39W
Socket:	G5
Туре:	FDH-39
Luminous Flux (Im):	3500lm
Colour Rendering:	85
Colour temperature (K):	6500K
Category:	FLUO
Number:	2
Number.	<u> </u>



COLOUR



Lbs:	T16
Watt:	39W
Socket:	G5
Туре:	FDH-39
Luminous Flux (Im):	3100lm
Colour Rendering:	85
Colour temperature (K):	3000K

LUMINAIR

Power Supply: Watt: Voltage: Luminous Flux (Im): CCT: Dimmable

ly: Electronic Integrated 78W + 78W 220V-240V ux (Im): 6650+7000Im 3000+6500K

ACCESSORIES

NO IMAGE AVAILABLE

ALTROVE 600 KIT SOSP/ALIM.DIMM 1541010A